

## Features

- UL<sup>®</sup> 1069 Listed
- Simple, push-button calling
- Call-placed indicator
- Cancel push button
- Call activates lamp on annunciator panel and corridor light
- Flame retardant (UL<sup>®</sup> 94V-0) plastic faceplate
- Corridor zone light capability

## Description

The SF101C Room Station incorporates push-button operation of call and cancel functions. A call is registered at the annunciator panel and on a corridor light or corridor zone light (if installed) when the call switch with integral call-placed LED is pushed. The call-placed LED will also illuminate. Calls are canceled by simply depressing the cancel button. The call-placed LED will also be extinguished. All station components are mounted on a rugged UL<sup>®</sup> 94V-0 plastic faceplate.

## Listings



UL<sup>®</sup> 1069 listed; UL<sup>®</sup> File Number E71599.



SF101C Audible-Visual Room Station

## Specifications

Dimensions:	Height:	4.50"	(114 mm)
	Width:	2.75"	(69 mm)
	Depth:	1.75"	(44 mm)
	Projects:	0.4375"	(11 mm)
		from mounting surface	
Construction:	Flame retardant (UL <sup>®</sup> 94V-0) plastic faceplate. Switches and electronic components are circuit board mounted.		
Connections:	Plug-in connectors.		
Housing:	Single gang ring, or single gang ring with double gang box.		

## Required Components

Tek-CARE<sup>®</sup> NC110 Nurse Call System